

SOIT402

1. Descrizione prodotto

Linea vita temporanea a cinghia completa di sacca di trasporto, cricchetto e connettori per il fissaggio. Può essere installata fissando le estremità alla struttura portante oppure a due punti d'ancoraggio in classe A1. Prima dell'utilizzo è necessario verificare la tenuta degli ancoraggi e il tirante d'aria, tenendo conto del numero degli operatori connessi simultaneamente alla linea.

Omologata per 2 operatori.

2. Caratteristiche

Materiale:	poliestere a basso allungamento
Lunghezza:	da 2 a 20 m.
Carico di rottura:	< 4000 daN
Connettori:	2 art. SOIT502.
Peso:	1,3 Kg
Conforme alla norma:	EN795 Classe C.

1. Product description

Temporary strap life line complete with transport bag, ratchet key and connectors for fastening. It can be installed by fastening to the end of the bearing structure or to the two class A1 anchor points. Before use, anchoring and air draft tightness must be verified, keeping in mind the number of operators connected simultaneously to the line.

Approved for 2 operators.

2. Features

Material:	low elongation polyester
Length:	from 2 to 20 m
Tensile strength:	< 4000 daN
Connectors:	2 art. SOIT502.
Weight:	1.3 Kg
In compliance with:	EN795 Class C.

